



- Raspon: 9,80 m (mjereno od sredine)
- Razmak među stupovima: 4m (mjereno od sredine)
- Broj okvira: 3
- Broj stupova: 6
- Ugrađeni limeni žljebovi za odvod oberinskih voda
- Korisna površina: 833,5 x 957,5 cm
- Pokrov: termoizolacioni panel

**ANAMARIA BADROIU BLA**  
dipl. ing. IT  
CIVILITATEA ARHITECTUR  
4-3302

 <b>BOLD d.o.o.</b> Kraljev 25, Zagreb OIB: 4096566660	Naziv: <b>GLAVNI PROJEKT</b>	Glavni projektant: <b>JAKOV BURAZIN, mag.ing.aedf.</b>	ZOP: <b>2/19</b> Datum: <b>2/19</b>
Izvođač: <b>GRAD GOSPIĆ</b> (brojka: 51.000-0200) OIB: 23300350	Projektant: <b>ARHITEKTONSKI PROJEKT</b>	Projektat: <b>ANAMARIJA BADROV BLAČ, dipl.ing.arh.</b>	Datum: <b>03.2019.</b> Broj: <b>1/50</b> Broj predloga: <b>1</b>
Gradnja: <b>REKONSTRUKCIJA DVORIŠTE ZA KOMUNALNI OTPAĐ GRAD GOSPIĆA</b>	Sažetak: <b>OBJEKT ZA SMJEŠTAJ OPREME - TOKLET I PRESJEKI</b>	Suradnik: <b>SANJA KOZULIĆ, mag.ing.aedf.</b>	Broj: <b>1</b> Verzija: <b>9</b>